



# Form 16—Inspection Certificate/Aspect Certificate/QBCC Licensee Aspect Certificate

[Version 5 – July 2017]

**NOTE: This form is to be used for the purposes of section 10(c) and 239 of the *Building Act 1975* and/or sections 32, 35B, 43, 44 and 47 of the *Building Regulation 2006*.**

**1. Indicate the type of certificate**

The stages of assessable building work are listed in section 24 of the Building Regulation 2006 or as conditioned by the building certifier.

An aspect of building work is part of a stage (e.g. waterproofing).

**Inspection Certificate** for

**Stage of building work** (for single detached class 1a or class 10 building or structure)

(indicate the stage)

\_\_\_\_\_

**Aspect of building work**

(indicate the aspect)

\_\_\_\_\_

**QBCC Licensee Aspect Certificate**

**Scope of the work**

Scope of the work covered by the licence class under the *Queensland Building and Construction Commission Regulation 2003* for the aspect being certified, e.g. scope of work for a waterproofing licence is "installing waterproofing materials or systems for preventing moisture penetration". An aspect being certified may include "wet area sealing to showers".

Fire Hose Reels



**2. Property description**

**PLEASE REFER TO THE  
DECISION NOTICE FOR  
DETAILS.**

**Street address** (include no., street, suburb/locality and postcode)

**Lot and plan details** (attach list if necessary)

**In which local government area is the land situated?**

**3. Building/structure description**


**PLEASE REFER TO THE  
DECISION NOTICE FOR  
DETAILS.**

**Building/structure description**

**Class of building/structure**

LOCAL GOVERNMENT USE ONLY

DATE RECEIVED		REFERENCE NUMBER/S	
---------------	--	--------------------	--

<p><b>4. Description of component/s Certified.</b></p> <p>Clearly describe the extent of work covered by this certificate, e.g. all structural aspects of the steel roof beams.</p> <p><b>PLEASE TICK TO INDICATE THOSE ELEMENTS COVERED UNDER THIS CERTIFICATE</b></p>	<p>Provision, installation, test and commissioning of fire hose reels including that:</p> <table border="1"> <tr> <td><input type="checkbox"/></td> <td>The general installation of Fire Hose Reels has been completed in accordance with the Australian Standard.</td> </tr> <tr> <td><input type="checkbox"/></td> <td>The hose reels have been installed in the locations shown on the approved plans.</td> </tr> <tr> <td><input type="checkbox"/></td> <td>Externally located hose reels have been provided with a weather and UV resistant cover.</td> </tr> <tr> <td><input type="checkbox"/></td> <td>The commissioning procedures have been completed as detailed in the Australian Standard.</td> </tr> <tr> <td><input type="checkbox"/></td> <td>Any valve that can prevent flow of water to a hose reel is padlocked in the open position and is marked with an attached, corrosion-resistant, durable tag, with the following in nominal 8 mm upper case text: FIRE SERVICE VALVE CLOSE ONLY TO SERVICE FIRE HOSE REELS</td> </tr> <tr> <td><input type="checkbox"/></td> <td>That a single fire hose reel (or the two most hydraulically disadvantaged fire hose reels operating simultaneously) plus any probable simultaneous flow, achieves a minimum discharge rate (with the nozzle in jet mode) of: <ul style="list-style-type: none"> <li>• 0.33L/s for a 19mm nom. dia. hose with 25mm nom. dia. supply pipe; and/or</li> <li>• 0.41L/s for a 25mm nom. dia. hose with 25mm nom. dia. supply pipe.</li> </ul> </td> </tr> </table>	<input type="checkbox"/>	The general installation of Fire Hose Reels has been completed in accordance with the Australian Standard.	<input type="checkbox"/>	The hose reels have been installed in the locations shown on the approved plans.	<input type="checkbox"/>	Externally located hose reels have been provided with a weather and UV resistant cover.	<input type="checkbox"/>	The commissioning procedures have been completed as detailed in the Australian Standard.	<input type="checkbox"/>	Any valve that can prevent flow of water to a hose reel is padlocked in the open position and is marked with an attached, corrosion-resistant, durable tag, with the following in nominal 8 mm upper case text: FIRE SERVICE VALVE CLOSE ONLY TO SERVICE FIRE HOSE REELS	<input type="checkbox"/>	That a single fire hose reel (or the two most hydraulically disadvantaged fire hose reels operating simultaneously) plus any probable simultaneous flow, achieves a minimum discharge rate (with the nozzle in jet mode) of: <ul style="list-style-type: none"> <li>• 0.33L/s for a 19mm nom. dia. hose with 25mm nom. dia. supply pipe; and/or</li> <li>• 0.41L/s for a 25mm nom. dia. hose with 25mm nom. dia. supply pipe.</li> </ul>
<input type="checkbox"/>	The general installation of Fire Hose Reels has been completed in accordance with the Australian Standard.												
<input type="checkbox"/>	The hose reels have been installed in the locations shown on the approved plans.												
<input type="checkbox"/>	Externally located hose reels have been provided with a weather and UV resistant cover.												
<input type="checkbox"/>	The commissioning procedures have been completed as detailed in the Australian Standard.												
<input type="checkbox"/>	Any valve that can prevent flow of water to a hose reel is padlocked in the open position and is marked with an attached, corrosion-resistant, durable tag, with the following in nominal 8 mm upper case text: FIRE SERVICE VALVE CLOSE ONLY TO SERVICE FIRE HOSE REELS												
<input type="checkbox"/>	That a single fire hose reel (or the two most hydraulically disadvantaged fire hose reels operating simultaneously) plus any probable simultaneous flow, achieves a minimum discharge rate (with the nozzle in jet mode) of: <ul style="list-style-type: none"> <li>• 0.33L/s for a 19mm nom. dia. hose with 25mm nom. dia. supply pipe; and/or</li> <li>• 0.41L/s for a 25mm nom. dia. hose with 25mm nom. dia. supply pipe.</li> </ul>												
<p><b>5. Basis of certification</b></p> <p>Detail the basis for giving the certificate and the extent to which tests, specifications, rules, standards, codes of practice and other publications, were relied upon.</p>	<p>Compliance with the Approved Plans, Conditions of the Decision Notice appurtenant to the Development Approval for Building Work and the Building Act 1975 inclusive of the National Construction Code Vol 1 Parts E and AS 2441 - 2005.</p>												
<p><b>6. Reference documentation</b></p> <p>Clearly identify any relevant documentation, e.g. numbered structural engineering plans.</p>	<p>Those plans and/or specifications relevant to the Development Approval for Building Works stamped approved and bearing Pacific BCQ's Reference Number shown below.</p>												
<p><b>7. Building certifier reference number and development approval number</b></p>	<table border="1"> <tr> <td><b>Building certifier reference number</b></td> <td><b>Development approval number</b></td> </tr> <tr> <td></td> <td>N/A</td> </tr> </table>	<b>Building certifier reference number</b>	<b>Development approval number</b>		N/A								
<b>Building certifier reference number</b>	<b>Development approval number</b>												
	N/A												
<p><b>8. QBCC licensee details</b></p> 	<p><b>Name (in full)</b></p> <p>_____</p> <p><b>Company name if applicable</b>                      <b>Contact person</b></p> <p>_____    _____</p> <p><b>Phone no. (business hours)</b>    <b>Mobile no.</b>                      <b>Fax no.</b></p> <p>_____                                      _____                                      _____</p> <p><b>Email address</b></p> <p>_____</p> <p><b>Postal address</b></p> <p>_____</p> <p><b>Licence class</b>    <b>Licence number</b></p> <p>_____    _____</p> <p><b>Date approval to inspect received from building certifier</b></p> <p>N/A</p>												
<p><b>9. Signature of QBCC licensee</b></p>	<table border="1"> <tr> <td><b>Signature</b></td> <td><b>Date</b></td> </tr> <tr> <td>_____</td> <td>_____</td> </tr> </table>	<b>Signature</b>	<b>Date</b>	_____	_____								
<b>Signature</b>	<b>Date</b>												
_____	_____												